



SINGLE STAGE BACK PULL-OUT END-SUCTION CENTRIFUGAL PUMP: PA

General Data



PARAGON PUMP Company was founded by a dedicated pump professional with over 30 years of worldwide experience. The company's goal is to provide high quality products at extreme competitive prices supported by the best customer service in the industry.

To assure high quality, performance and reliability, Paragon Pumps are manufactured to international standards in facilities with ISO 9001 certification. Paragon Pump backs up its commitment to quality with a full one-year (12 months) warranty.



PA SERIES

The Paragon PA Series pumps meet the DIN 24255 specification for end suction, horizontal centrifugal pumps. The PA Series offers many features and benefits that improve performance, increase reliability and reduce maintenance time and cost.

- Heavy-duty cast iron casing with integral cast feet suitable for 10 bar working pressure. Also available for working pressures up to 16 bar. Centreline discharge assures that the casing is self-venting.
- Flanges to ISO 2048 PN16 as standard. Also available with ASA125# or JIS 10k drilling.
- Back pull out design for fast and easy maintenance when fitted with a spacer type coupling because suction and discharge piping and drive motor remain in place.
- Maximum interchangeability for low spare parts inventory with four bearing frames and four shaft sizes for 50 sizes of pumps.
- Replaceable wear rings to assure optimum efficiency and performance at all times.
- Shaft seal is available as packing or as mechanical seal to suit all types of applications.
- Double shrouded, hydraulically balances impellers with back vanes to minimize gland pressure in cast iron or bronze as standard. Also available in stainless steel or zinc free bronze.
- Heavy-duty cast iron bearing housing with greased ball bearings as standard. Also available with oil lubricated bearings.
- Heavy-duty shaft in stainless steel for longer life and to assure product purity.
- Stainless steel shaft sleeve for product purity, longer mechanical seal life and to prevent damage to the shaft from packing or the mechanical seal.
- Operating temperature from -10°C to 105°C as standard. Available for up to 160°C with cooling and suitable mechanical seal selection.
- Suitable for both 50 cycle and 60 cycle speeds up to 3500rpm.

APPLICATIONS

PARAGON PA Series pumps can be used for the following services in the Commercial, Residential, Agricultural, Industrial, Process, Petroleum and Food & Beverage industries.

- Air Conditioning
- Fire Protection
- Plumbing
- Circulating
- Transfer
- Pressure Boosting
- Cooling Towers
- Irrigation
- Water Treatment & Supply



TECHNICAL INFORMATION

Design : DIN 24255

Operating pressure : 1000 kpa standard, 1600 kpa optional.

Hydrostatic Test pressure : 1500 kpa standard, 2400 kpa optional.

Operation temperature : -10°C to 105°C standard, 160°C optional.

Operation speeds :


50 Hz, 1450 and 2900 rpm.

60 Hz, 1750 and 3500 rpm.

MATERIALS OF CONSTRUCTION

	BRONZE FITTED (BF)	ALL IRON (AI)	STAINLESS STEEL (SS)
Casing	Cast Iron	Cast Iron	Stainless Steel
Impeller	Bronze	Cast Iron	Stainless Steel
Wear Ring	Bronze	Cast Iron	Stainless Steel
Shaft	Stainless Steel	Carbon Steel	Stainless Steel
Shaft Sleeve	Stainless Steel	Stainless Steel	Stainless Steel
Gland	Cast Iron	Cast Iron	Stainless Steel

PA SERIES fully complies to both performance and dimensional standards for the International Standard **DIN 24255**



1. BEARING HOUSING

Rugged cast iron construction with four bearing housing covering the complete range of fifty pumps for maximum interchangeability.

2. STUFFING BOX

Standard stuffing box includes gland packing and lantern ring with internal flushing or single mechanical seal with internal or external flush.

3. SHAFT

One piece stainless steel shaft in four sizes covering the complete range of fifty pumps for maximum interchangeability.

4. CASING

The cast iron volute casing is heavy duty design with integrally cast feet, vertical top centreline discharge and axial suction nozzle with cast inlet vane to improve flow into the impeller and reduce required NPSH.

5. IMPELLER

Double shrouded type, hydraulically balanced and positive drive shaft key and domed impeller lock nut.

6. WEAR RINGS

Replaceable wear rings are standard on all casings and on rear covers for larger pumps which assures hydraulic performance and reduces maintenance time and cost.

7. SHAFT SLEEVE


Replaceable fully machined, positively driven, hook type stainless steel shaft sleeve prevents damage to the shaft from gland packing or mechanical seal and reduces maintenance cost.

8. SUPPORT FOOT


Removable and adjustable support foot provides added rigidity and ease of maintenance.

9. BEARINGS

All pumps come with grease lubricated ball bearings as standard. Permanently, sealed greased bearings or oil lubricated bearing also available.




FLANGES DRILLED TO DIN 2332 PN 16 RF





PUMP SIZE	BEARING HOUSING	SUCTION	DISCHARGE	PUMP DIMENSIONS														SHAFT END		NET WEIGHT
				a	f	h1	h2	b	m1	m2	n1	n2	n3	h3	øS1	øS2	w	d	l	KG
32-13	25	50	32	80	360	112	140	50	100	70	190	140	100	14	14	14	267	24	50	29
32-16	25	50	32	80	360	132	160	50	100	70	240	190	100	14	14	14	267	24	50	35
32-20	25	50	32	80	360	160	180	50	100	70	240	190	110	14	14	14	267	24	50	47
32-26	25	50	32	100	360	180	225	65	125	95	320	250	110	14	14	14	267	24	50	58
40-13	25	65	40	80	360	112	140	50	100	70	210	160	100	14	14	14	267	24	50	31
40-16	25	65	40	80	360	132	160	50	100	70	240	190	100	14	14	14	267	24	50	34
40-20	25	65	40	100	360	160	180	50	100	70	265	212	110	14	14	14	267	24	50	45
40-26	25	65	40	100	360	180	225	65	125	95	320	250	110	14	14	14	267	24	50	61
40-32	35	65	40	125	470	200	250	65	125	95	345	280	110	14	14	14	342	32	80	94
40-32G	45	65	40	125	526	200	250	65	125	95	345	280	110	14	14	14	367	42	110	105
50-13	25	65	50	100	360	132	160	50	100	70	240	190	100	14	14	14	267	24	50	35
50-16	25	65	50	100	360	160	180	50	100	70	265	212	110	14	14	14	267	24	50	39
50-20	25	65	50	100	360	160	200	50	100	70	265	212	110	14	14	14	267	24	50	49
50-32	35	65	50	125	470	225	280	65	125	95	345	280	110	18	14	14	342	32	80	113
50-32G	45	65	50	125	526	225	280	65	125	95	345	280	110	18	14	14	367	42	110	105
65-13	25	80	65	100	360	160	180	65	125	95	280	212	110	14	14	14	267	24	50	41
65-16	25	80	65	100	360	160	200	65	125	95	280	212	110	14	14	14	267	24	50	47
65-20	25	80	65	100	360	180	225	65	125	95	320	250	110	14	14	14	267	24	50	55
65-26	35	80	65	100	470	200	250	80	160	120	360	280	110	15	18	14	342	32	80	87
65-32	35	80	65	125	470	225	280	80	160	120	400	315	110	18	18	14	342	32	80	110
65-32G	45	80	65	125	525	225	280	80	160	120	400	315	110	18	18	14	367	42	110	120
80-16	25	100	80	125	360	180	225	65	125	95	320	250	110	14	14	14	267	24	50	53
80-20	35	100	80	125	470	180	250	65	125	95	345	280	110	15	14	14	342	32	80	76
80-26	35	100	80	125	470	200	280	80	160	120	400	315	110	15	18	14	342	32	80	95
80-32	35	100	80	125	470	250	315	80	160	120	400	315	110	16	18	14	342	32	80	118
80-32G	45	100	80	125	526	250	315	80	160	120	400	315	110	16	18	14	367	42	110	130
80-40	45	100	80	125	530	280	355	83	160	120	440	340	110	18	18	14	370	42	110	160
100-16	35	125	100	125	470	200	250	80	160	120	360	280	110	15	18	14	342	32	80	87
100-20	35	125	100	125	470	200	280	80	160	120	360	280	110	16	18	14	342	32	80	102
100-26	35	125	100	140	470	225	280	80	160	120	400	315	110	16	18	14	342	32	80	102
100-32	35	125	100	140	470	250	315	80	160	120	400	315	110	16	18	14	342	32	80	118
100-32G	45	125	100	140	526	250	315	80	160	120	400	315	110	16	18	14	367	42	110	130
100-40	45	125	100	140	530	280	355	100	200	150	500	400	110	20	23	14	370	42	110	176
125-20	35	150	125	140	470	250	315	80	160	120	400	315	110	16	18	14	342	32	80	112
125-26	35	150	125	140	470	250	355	80	160	120	400	315	110	16	18	14	342	32	80	117
125-32	45	150	125	140	530	280	355	100	200	150	500	400	110	18	23	14	370	42	110	155
125-40	45	150	125	160	530	315	400	100	200	150	500	400	110	18	23	14	370	42	110	178
125-50	55	150	125	160	670	355	450	100	200	150	550	450	110	25	23	14	500	48	110	300
150-20	35	200	150	160	500	280	400	100	200	150	400	315	110	18	23	14	369	32	80	132
150-26	45	200	150	160	530	250	355	100	200	150	450	350	110	18	23	14	370	42	110	163
150-32	45	200	150	160	530	280	400	100	200	150	550	450	110	18	23	14	370	42	110	170
150-40	45	200	150	160	530	315	450	100	200	150	550	450	110	18	23	14	370	42	110	207
150-50	55	200	150	180	670	375	500	100	200	150	550	450	110	22	23	14	500	48	110	330
200-26	45	250	200	180	555	315	450	100	200	150	550	450	110	20	28	14	392	42	110	219
200-32	55	250	200	180	670	315	480	120	220	170	600	480	110	20	28	14	505	48	110	286
200-40	55	250	200	180	670	335	480	120	250	170	600	480	110	20	28	14	505	48	110	328
200-50	65	250	200	200	720	425	560	100	200	150	660	560	140	22	23	19	515	60	140	450
250-32	55	300	250	220	691	355	520	150	250	200	660	510	110	26	28	14	525	48	110	366
250-40	55	300	250	220	682	400	560	150	250	200	660	510	110	26	28	14	516	48	110	396
250-50	65	300	250	250	720	450	670	120	240	190	750	650	140	32	23	19	515	60	140	550
300-40	65	350	300	300	720	425	670	120	250	190	760	650	140	30	30	19	515	60	140	550

Dimensions in mm

D	OD	B	F	N	S	PCD
32	140	18	2	4	18	100
40	150	18	3	4	18	110
50	165	20	3	4	18	125
65	185	20	3	4	18	145
80	200	22	3	8	18	160
100	220	24	3	8	18	180
125	250	26	3	8	18	210
150	285	26	3	12	22	240
200	340	30	3	12	22	295
250	405	32	3	12	26	350
300	460	32	4	12	26	410
350	520	32	4	16	26	470
400	580	34	4	16	30	525





PARAGON PUMP (ASIA) PTE LTD

37, Kallang Pudding Road, #08-08
Tong Lee Building Block B, Singapore 349315
Tel : 6841 2818 Fax : 6841 5988